

*ETITEC M T12 300/12,5 4+0



Specificatii

Cod ETI	002440509
Descriere	*ETITEC M T12 300/12,5 4+0
Denumire clasă	Protec ie supratensiuni
Tip	T1, T2
AC max continuous operating voltage Uc	300V
In (8/20)	20kA
Parte superioara - Nivel de protectie a tensiunii (kV)	1.5kV
Curent de scurgere	DA
Tehnologie aplicata	MOV
Semnalare la distan ă	NU
Sistem re ea	TN-S
Numarul de module	4
Adancime incorporata (mm)	70mm
Func ie	SPD
Grup Catalog	ETITEC M

Pagina de produse online 

Alta documentatie



ETIM clasificare internațională

Clasificare	EC001457
Denumire clasă	Combined arrester for power supply systems
System configuration DC	Nu
System configuration IT	Nu
System configuration TN-C	Nu
System configuration TN-S	Da
System configuration TT	Nu
System configuration other	Nu
Number of poles	4
Lightning impulse current (10/350 μs)	12,5
Max. continuous voltage AC	300
Nominal voltage AC	230
Voltage protection level	1,5
Specific energy (W/R)	39
Max. conductor cross section solid (solid, stranded)	35
Max. conductor cross section flexible (fine-strand)	25
Mounting method	DIN rail (top hat rail) 35 mm
Construction size	4 modular spacing
Remote signalling	Nu
Signalling at the device	Optical
Test class	Type 1 + 2
Exhausting	Nu
Integrated backup fuse	Nu
Degree of protection (IP)	IP20