

*KZS-1M-DN 1p+N A B20/0.03 6kA



Specificatii

Cod ETI	002175145
Descriere	*KZS-1M-DN 1p+N A B20/0.03 6kA
Denumire clasă	Disjunctor cu protecție diferențială (RCBO)
Curent nominal (A)	20A
Tip	A
Curent de defect nominal (A)	0.03A
Caracteristică de întrerupere	B
Număr de poli	1+N
Capacitatea de rupere (kA)	6kA
Secțiune transversală nominală	1mm ² -10mm ²
Standarde	IEC 61009

Pagina de produse online [🔗](#)

Alta documentatie



Catalog caracteristici tehnice

Model 3D

2D mușchi

Manual de instrucțiuni

Declarație CE

Eplan mușchi

ETIM clasificare internationala

Clasificare	EC000905
Denumire clasă	Earth leakage circuit breaker
Number of poles (total)	2
Number of protected poles	1
Rated voltage	230V
Rated current	20A
Rated fault current	0,03A
Leakage current type	A
Current limiting class	3
Rated short-circuit breaking capacity according to EN 61009	6kA
Rated short-circuit breaking capacity according to IEC 60947-2	6kA
Voltage type	AC
Frequency	Other
Release characteristic	B
Concurrently switching neutral conductor	Da
Width in number of modular spacings	1
Degree of protection (IP)	IP20
Connectable conductor cross section multi-wired	1...10mm ²