

EDBJ-4x25-4x25/N



Specificatii

Cod ETI	001102429
Descriere	EDBJ-4x25-4x25/N
Denumire clasă	Bloc distribu ie
Tip montaj	TH 35
Curent nominal (A)	100A
Tensiune nominală AC (V)	415V
Tensiune nominală DC (V)	415V
Tensiune nominala de izolare (V)	1000V
Capacitatea de rupere (kA)	10kA
Înăl îime (mm)	80.3mm
Lă îime (mm)	17.8mm
Adâncime (mm)	50mm
Sec iune transversală nominală	2.5mm ² -25mm ²
Materialul corpului	PC/ABS
Materialul clemei	MO-58
Temperatura de operare (°C)	-30°C-80°C

Pagina de produse online 

Alta documentatie



Catalog caracteristici tehnice

Model 3D

2D mușchi

Declaratie CE

Eplan mușchi

ETIM clasificare internationala

Clasificare	EC001284
Denumire clasă	Single- and multi-pole terminal strip
Connectable conductor cross section solid-core	2.5...25mm ²
Rated current I _n	100A
Rated voltage	415V
Type of electrical connection 1	Screw connection
Number of poles	1
Number of clamp positions per pole	8
Mounting method	Other
Material insulation body	Thermoplastic
Operating temperature	-30...80°C
Inflammability class of insulation material according to with UL94	V0
Closing plate required	Nu
Colour	Blue