

ETITEC ML T123 300/12,5 2+0



Specificatii

Cod ETI	002440663
Descriere	ETITEC ML T123 300/12,5 2+0
Denumire clasă	Protec ie supratensiuni
Tip	T1, T2, T3
AC max continous operating voltage Uc	300V
I imp(10/350) Curent de Impuls [kA]	12.5kA
In (8/20)	20kA
I _{max} (8/20) [kA]	40kA
Parte superioara - Nivel de protectie a tensiunii (kV)	1.5kV
Curent de scurgere	DA
Tehnologie aplicata	MOV
Semnalare la distan ă	NU
Sistem re ea	TN-S
Numarul de module	2
Adancime incorporata (mm)	70mm
Func ie	SPD
Grup Catalog	ETITEC ML

[Pagina de produse online](#)

Alta documentatie

[Catalog caracteristici tehnice](#)[Model 3D](#)[2D mușchi](#)[Manual de instructiuni](#)[Declaratie CE](#)[Eplan mușchi](#)

ETIM clasificare internațională

Clasificare	EC001457
Denumire clasă	Combined arrester for power supply systems
System configuration DC	Nu
System configuration IT	Nu
System configuration TN-C	Nu
System configuration TN-S	Da
System configuration TT	Nu
System configuration other	Nu
Number of poles	2
Lightning impulse current (10/350 μs)	12,5
Max. continuous voltage AC	300
Nominal voltage AC	230
Voltage protection level	1,5
Specific energy (W/R)	39
Max. conductor cross section solid (solid, stranded)	35
Max. conductor cross section flexible (fine-strand)	25
Mounting method	DIN rail (top hat rail) 35 mm
Construction size	2 modular spacing
Remote signalling	Nu
Signalling at the device	Optical
Test class	Type 1 + 2
Exhausting	Nu
Integrated backup fuse	Nu
Degree of protection (IP)	IP20