

Data Sheet | Item Number: 709-583

Priză dulap aparataj de comutație; pentru șină DIN și montare cu șurub; pentru conector, tip F, CEE 7/4 (Schuko); obișnuit în DE, NL, AT; cu indicator de stare cu LED; cu conectare dublă Push-in Cage Clamp; roșu

<https://www.wago.com/709-583>



Notes

Safety information	Installation must be performed by a qualified electrician.
Safety information 2	During the insulation resistance test, the active conductors must be connected. The integrated status indicator in the control cabinet outlet must be protected against transient overvoltages. Overvoltage protection in low-voltage systems must be observed.

Technical data

Number of spacings	3 -ori
Mounting type	DIN-35 rail
Safety information	Installation must be performed by a qualified electrician.

Electrical data

Power loss P_I (note)	LED status indication and contact resistance
Power loss P_I (max.)	1.8 W
Rated current	16 A

Connection data

Connection technology	Push-in CAGE CLAMP®
Strip length	9 ... 10 mm / 0.35 ... 0.39 inci
Solid conductor	0,2 ... 2,5 mm ² / 24 ... 14 AWG
Fine-stranded conductor	0,2 ... 2,5 mm ² / 24 ... 14 AWG
Fine-stranded conductor; with insulated ferrule	2,5 mm ² / 14 AWG
Stranded conductor	0,2 ... 2,5 mm ² / 24 ... 14 AWG

Physical data

Width	45 mm / 1.772 inci
Height	65 mm / 2.559 inci
Height from upper-edge of DIN-rail	59,8 mm / 2.354 inci
Height from the surface	65 mm / 2.559 inci
Depth	84,7 mm / 3.335 inci

Material data

Color	roșu
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0 MJ
Contact material	Copper alloy
Contact plating	Sn
Clamping spring material	Chrome-nickel spring steel (CrNi)
Weight	0.1 kg



Commercial data		
eCl@ss 10.0		27-14-23-05
eCl@ss 9.0		27-14-23-05
ETIM 8.0		EC001663
ETIM 7.0		EC001663
PU (SPU)		1 Buc.
Packaging type		Box
Country of origin		BG
GTIN		4055143718301
Customs tariff number		85366990990

Environmental Product Compliance		
RoHS Compliance Status		Compliant,No Exemption