



SM damp area distributor IP65, NEPTUN

Order number: 7270004
Type: NEPTUN48

- NEPTUN - Seeks the challenge. - Masters every situation.
- Protects equipment from harmful ingress of water and dust - IP65
 - Tool-free cable entry due to IP65 membrane entry flange
 - Reduced condensation due to integrated ventilation system
 - Tool-less adjustable top-hat rail due to click system
 - Robust housing for harsh conditions
 - 1- to 4-row executions
 - For high requirements SQ variant

Dimensions		Environmental conditions	
Depth	150 mm	Ambient temperature (24h)	35 °C
Height	715 mm	Ambient temperature (maximum)	40 °C
Width	310 mm	Ambient temperature (minimum)	-25 °C
		Max. rel. humidity at 25°C (short term)	90 %
		Max. rel. humidity at 40°C	50 %
Material			
Door material	PC		
Housing material	PS		

Properties

Can be lead sealed	true
Colour	Grey
Degree of protection (IP)	IP65
Halogen-free	true
Impact resistance	IK08
Installation type	SM
Insulation	Protection class II
Number of compartments	48
Number of rows	4

Technical features

Design current	63 A
Design voltage	AC 400V / AC 1000V / DC 1500V *
Total inserts	28x Ø 5-12 mm 14x Ø 5-15 mm 8x Ø 6-20 mm 2x Ø 8-26 mm 2x M32/M50 4x M20 6x M25

Certificates & standards

CE	true
Glow wire test	650 °C
REACH	true
RoHS	true
Standards	• DIN EN 60670-1 • DIN EN 60670-24 • DIN 43871
VDE	true

Accessories

Equipped with	1x N-N plug-in clamp (SKN17N) 1x PE plug-in clamp (SKPE34) 1x cable cover (NKB) 2x cover strip (ADS12gr)
---------------	---