



**HW Device connection socket E117**

Order number: 7350096  
 Type: E117

- The basics for a proper hollow wall installation
- With break-outs for cables and pipes
  - Integrated management support for NYM cables
  - Secure fixing of tubes

| Dimensions            |            |
|-----------------------|------------|
| Depth                 | 61 - 61 mm |
| Diameter              | 68 mm      |
| Internal depth        | 60 mm      |
| Milling hole diameter | Ø 68 mm    |

| Environmental conditions                |        |
|-----------------------------------------|--------|
| Ambient temperature (24h)               | 35 °C  |
| Ambient temperature (maximum)           | 40 °C  |
| Ambient temperature (minimum)           | -25 °C |
| Max. rel. humidity at 25°C (short term) | 90 %   |
| Max. rel. humidity at 40°C              | 50 %   |

| Material        |    |
|-----------------|----|
| Socket material | PP |

Properties

|                           |        |
|---------------------------|--------|
| Can be lead sealed        | -      |
| Colour                    | Orange |
| Degree of protection (IP) | IP30   |
| Free of heavy metals      | true   |
| Halogen-free              | -      |
| Installation type         | HW     |
| PVC-free                  | true   |
| Silicone-free             | true   |
| Stackable                 | -      |
| Weather-resistant         | -      |

Technical features

|                              |         |
|------------------------------|---------|
| Cable entry 3x1.5²           | 4       |
| Cable entry 7x1.5²/5x2.5²    | 2       |
| Design voltage               | 400 V   |
| max. cross section           | 2,5 mm² |
| Pipe entry M20               | 4       |
| Suitable for sheet thickness | 5-40 mm |

Certificates & standards

|                |                                                                                                                      |
|----------------|----------------------------------------------------------------------------------------------------------------------|
| CE             | true                                                                                                                 |
| Glow wire test | 850 °C                                                                                                               |
| REACH          | true                                                                                                                 |
| RoHS           | true                                                                                                                 |
| Standards      | <ul style="list-style-type: none"><li>• DIN EN 60670-1(VDE 0606-1)</li><li>• DIN EN 60670-22 (VDE 0606-22)</li></ul> |
| VDE            | true                                                                                                                 |

Accessories

|               |      |
|---------------|------|
| Equipped with | None |
|---------------|------|