



HW/FM small distributor JUMBO

Order number: 7250017
Type: JUMBO24+4

Flexible usage - Flush mounted and hollow wall

- Generous wiring space
- Strain relief possible
- Frame height 9mm
- Packaging can be used as plaster protection
- Suitable with HWA-Set for hollow wall installation (Art.No. 7290079)

suitable for:

Dimensions		Environmental conditions	
Depth	98 mm	Ambient temperature (24h)	35 °C
Height	525 mm	Ambient temperature (maximum)	40 °C
Height of HW cut-out	485 mm	Ambient temperature (minimum)	-25 °C
Height of mounting recess	518 mm	Max. rel. humidity at 25°C (short term)	95 %
Plaster compensation	15 mm	Max. rel. humidity at 40°C	50 %
Width	365 mm		
Width of HW cut-out	323 mm		
Width of mounting recess	359 mm		
Material			
Box material	PS		
Cover material	PS		
Door material			

Properties

Can be lead sealed	true
Colour	White
Degree of protection (IP)	IP30
Free of heavy metals	true
Halogen-free	-
Impact resistance	IK07
Installation type	HW / UP
Insulation	Protection class II
Number of compartments	28
Number of rows	2
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

Technical features

Design current	63 A
Design voltage	400 V
Permissible power loss according to DIN 43 873	
Suitable for sheet thickness	10-45 mm

Certificates & standards

CE	true
Glow wire test	850 °C
REACH	true
RoHS	true
Standards	• DIN EN 60670-1 • DIN EN 60670-24 • DIN EN 61439-1 • DIN EN 61439-3 • DIN 43871
VDE	true

Accessories

Equipped with	1x door with frame (T+RJUMBO24+4) 1x FI additional terminal (FIK) 1x PE-N plug-in terminal (SKN17PE)
Recommended purchase	Hollow wall anchor set (HWA-Set) Wall claw set (MK-Set) Mounting bracket set (MH-Set) Cover strip (ADS12W)