

Field distributor

Order number: 7110221
 Type: FV3-3



- Large distributors for intelligent installation technology
- Generous cable entries at the bottom, top and back of each field width
 - Upper and lower cable entry with membrane puncture, allowing quick and easy handling without additional tools
 - All covers with lateral bulkheads
 - From three field widths with double door
 - Various lock variants are possible - even DIN cylinder lock
 - Incl. 1x ZSSKN17N and 1x ZSSKPE34 plug-in terminal per field

suitable for: Geräte bis Nennstrom 125A

Dimensions		Environmental conditions	
Depth	165 mm	Ambient temperature (24h)	35 °C
Height	500 mm	Ambient temperature (maximum)	40 °C
Width	800 mm	Ambient temperature (minimum)	-25 °C
		Max. rel. humidity at 25°C (short term)	95 %
		Max. rel. humidity at 40°C	50 %
Material			
Box material	Sheet steel powder-coated		
Cover material	PS		
Door material	Sheet steel powder-coated		

Properties

Can be lead sealed	true
Colour	White
Degree of protection (IP)	IP43
Free of heavy metals	true
Halogen-free	-
Installation type	SM
Insulation	Protection class II
Number of bays	3
Number of compartments	108
Number of rows	3
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

Technical features

Design voltage	400 V
Permissible power loss according to DIN 43 873	

Certificates & standards

CE	true
Glow wire test	750 °C
REACH	false
RoHS	true
VDE	-

Accessories

Equipped with	N-Steckklemme 6x25mm ² ; 28x4mm ² r PE-Steckklemme 3x25mm ² ; 14x4mm ² r 6 x Flansch mit Durchstoßmembran
---------------	---