One-gang junction box - ECON® Iso +



One-gang junction box ECON® Iso +

- for retrofitting in ETICS with wood fibre and rock wool insulation boards
- for insulation thicknesses of 60 mm and upwards
- 4 swivelling cutters for secure mechanical fastening
- 4 screw domes
- Sealing lip on all sides
- including centering aid
- including setting tool (Art. No.1090-22) per packaging unit

Article no:	**1159-55**
EAN:	4013456549302
Depth	55 mm
for insulation thicknesses	> 60 mm
Cut hole Ø	68 mm
Device screws	2
Screw spacing	60 mm
Cable entries of up to Ø 11.5 mm	4
Conduit entries M20	4
Combination distance	71 mm
Support connectors for each package	5
Protection class	IP 30
Glow wire	850 °C
Halogen-free	Yes
Packaging inner/dispatch	10/100

The ECON® Iso + one-gang junction box is the solution for electrical installation work in ETICS with wood fibre and rock wool insulation boards. Four swivels, specially designed for use in solid heat insulation and plaster base boards, ensure secure anchoring – also for retrofitting! The ECON® technology elastic sealing membrane guarantees air tightness and allows the toolless insertion of conduits or cables. This means that switches, sockets, intercoms and many more can be installed permanently and securely and heat bridge-free.

- Air-tight and heat bridge-free electrical installation in accordance with DIN 18015-5 in ETICS
- Suitable for wood fibre and rock wool ETICS from a gross density of 85kg/m³
- Secure mechanical anchoring in the ETICS thanks to 4 swivelling cutting edges
- Special cutter (Art. No. 1088-07) prevents damage to the cable
- Making of combinations is possible