Product datasheet
E117HF



HW Device connection socket E117HF

Order number: 7350166
Type: E117HF

The basics for a proper hollow wall installation

- With break-outs for cables and pipes
- Integrated cable restraint for NYM cables
- Secure fixing of tubes

Dimensions

Depth	62 - 62 mm
Diameter	68 mm
Internal depth	60 mm
Milling hole diameter	68 mm

Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	90 %
Max. rel. humidity at 40°C	50 %

Material

Socket material	PP

© f-tronic GmbH. All rights reserved
www.f-tronic.com

Properties

Can be lead sealed	false
Colour	White
Degree of protection (IP)	IP30
Free of heavy metals	true
Halogen-free	true
Installation type	Hollow wall
PVC-free	true
Silicone-free	true
Stackable	-

Technical features

Cable entry 3x1.5²	3
Cable entry 5x1.5²/3x2.5²	3
Cable entry 7x1.5²/5x2.5²	1
Design voltage	400 V
max. cross section	2,5 mm²
Pipe entry M20	1
Pipe entry M20/M25	2
Suitable for sheet thickness	5-40 mm

Certificates & standards

CE	true
Glow wire test	850 °C
REACH	false
RoHS	true
Standards	• DIN EN 60670-1 (VDE 0606-1) • DIN EN 60670-22 (VDE 0606-22)
VDE	true

Accessories

Equipped with	None

© f-tronic GmbH. All rights reserved
www.f-tronic.com