

FM Double socket box E400

Order number: 7310155
Type: E400

Installed faster thanks to the DUPLEX

- Optimally suited for opposite installation in 100 mm partition wall
- Combined with all FM socket boxes
- More wiring space
- Pipe and cable entries
- Expandable with levelling rings E130/E132
- One-man assembly

Dimensions	
Depth	100 - 100 mm
Internal depth	98 mm
Length	80 mm
Width	66 mm

Environmental conditions	
Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	90 %
Max. rel. humidity at 40°C	50 %

© f-tronic GmbH. All rights reserved
www.f-tronic.com

Properties

Can be lead sealed	-
Colour	Black
Degree of protection (IP)	IP20
Free of heavy metals	true
Halogen-free	true
Installation type	FM
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

Technical features

Cable entry	4 per page
Design voltage	400 V
max. cross section	2,5 mm²
Pipe entry M20	4 per page
Pipe entry M25	4 per page

Certificates & standards

CE	true
Glow wire test	650 °C
REACH	false
RoHS	true
Standards	• DIN EN 60670-1(VDE 0606-1) • DIN EN 60670-22 (VDE 0606-22)
VDE	true

Accessories

Equipped with	None

© f-tronic GmbH. All rights reserved
www.f-tronic.com